

Flood Luminaire

ULTRA-TECH™ Induction Lighting

PSUTF-100ZY, PSUTF-150ZY



Features

- Die cast aluminum housing with powder coated finish for corrosion-resistance.
- Anodized aluminum reflector and clear tempered glass lens are designed to optimize light distribution.
- Gas-tight silicon rubber seal made for wet locations.


Lamp and Ballast

- Ultra-Tech's 70W-100W rectangular tubular induction lamp features high lighting efficacy, 100,000 hours long lifetime with 5-year warranty, good color rendering, and stable output.
- Ultra-Tech's electronic ballast features high power factor (>0.95), flicker free, low loss and constant output.


Applications

- Billboards, buildings, parks, pools, parking lots, plazas, tennis courts.

Photometric



Dimensions Unit:in(mm)



Fixture Specifications

Fixture Model No.	Lamp	Wattage (W)	Rated Initial Luminance (Lm)	Voltage (V)	Color Temp (K)*	Ambient (°C/°F)	Installation	IP Class	Note	UL CUL
PSUTF-100ZY	ST70W	70	4900-5250	120-277	6500	-20 - 40+/-4 - 104+	Bracket	IP65	Upward	yes
	ST80W	80	5600-6000							
	ST100W	100	7500-8000							
PSUTF-150ZY	ST150W	150	11200-12000	120-277	6500	-20 - 40+/-4 - 104+	Bracket	IP65		yes

*Note: Color Temperature 2720-6500 available upon request.



pure_spectrum™

V. 1.1, 08/2010



www.PureSpectrum.com